

Package: mkde (via r-universe)

September 1, 2024

Type Package

Title 2D and 3D Movement-Based Kernel Density Estimates (MKDEs)

Version 0.3

Date 2024-07-02

Author Jeff A. Tracey, James Sheppard, Jun Zhu, Robert Sinkovits, Amit Chourasia, Glenn Lockwood, Matthew Wang, and Robert N. Fisher

Maintainer Robert Sinkovits <sinkovit@sdsc.edu>

Description Provides functions to compute and visualize movement-based kernel density estimates (MKDEs) for animal utilization distributions in 2 or 3 spatial dimensions.

License GPL (>= 3)

LazyLoad yes

Depends R (>= 3.5.0)

Imports Rcpp (>= 0.9.6), sf, terra, stars

LinkingTo Rcpp

NeedsCompilation yes

Date/Publication 2024-07-02 19:30:02 UTC

Repository <https://sinkovit.r-universe.dev>

RemoteUrl <https://github.com/cran/mkde>

RemoteRef HEAD

RemoteSha cfdc12fe01c90d80cf2f7e64f121e56a75634580

Contents

mkde-package	2
computeAreaRaster	4
computeContourValues	5
computeSizeMKDE	6
condor	8
deselectLocationsOutsideBounds	9

deselectNonMovementSteps	10
dugong	11
estVarMKDE	12
initializeAreaRaster	13
initializeDensity	14
initializeMKDE2D	15
initializeMKDE3D	17
initializeMovementData	18
mkde2Dgrid	20
mkde2Dinteraction	22
mkde3Dgrid	23
mkde3Dinteraction	25
mkdeToRaster	26
panda	28
plotMKDE	29
readdem_example	30
setMaximumZfromConstant	31
setMaximumZfromRaster	32
setMinimumZfromConstant	33
setMinimumZfromRaster	34
writeInterpolatedPathVTK	35
writeObservedLocationVTK	36
writeRasterToVTK	37
writeRasterToXDMF	39
writeToGRASS	40
writeToVTK	41
writeToXDMF	43

Index 45

mkde-package	<i>Movement-based kernel density estimates (MKDEs) in 2 or 3 spatial dimensions.</i>
--------------	--

Description

The mkde package enables animal space use to be estimated in three dimensions (3D) using data collected from biotelemetry tracking devices. This package addresses a recognized need in modeling animal space use (Belant et al. 2012) wherein researchers have been limited by the lack of 3D home range estimators. Animal space use can be characterized by the (x, y) spatial dimensions as well as a third z-dimension representing altitude, elevation, or depth for flying, terrestrial, or aquatic species, respectively. Although many biotelemetry devices record 3D location data with x, y, and z coordinates from tracked animals, the third z coordinate is typically not integrated into studies of animal spatial use. The mkde package enables users to visually explore the 3D MKDE volumes of animals to more intuitively understand how they are spatially related to the environmental covariates and bounding layers within their ranges, such as bathymetry or topography.

The mkde package builds on previous work on the Brownian bridge approach for estimating animal utilization distributions (Horne et al. 2007). This method, in contrast to location-based KDEs,

integrates kernels over time along a movement path interpolated between observed locations. Benhamou distinguished location-based kernel density estimators (LKDE) from movement-based kernel density estimators (MKDE), which includes Brownian bridge and biased random walk models. MKDEs account for time between consecutive observations in the estimator, do not requiring independent samples from the UD, and thus more realistically represent the space used by an animal. The user inputs animal location data typically obtained by a Global Positioning System (GPS) or Very High Frequency (VHF) device in which each observation includes an x-coordinate, a y-coordinate, a z-coordinate, and time. The observed locations are assumed to be subject to observation error and are normal random variables. The observation error variances are either provided by the manufacturers of the telemetry equipment or estimated from field trials, e.g., Hansen and Riggs (2008). Often, an animal's movement is limited in the z-dimension. For example, avian species are generally bounded below by the earth's surface, whereas marine animals are bounded below by the sea floor and above by the water's surface. Package functions allow the mkde user to bound the density in the z-dimension by $a(x,y)$ and $b(x,y)$ with a constant or a 2D raster.

The mkde package provides a 2.5D approach for computing home range area that essentially uses a 2D MKDE draped over a 2D elevation raster. The bias is corrected by calculating and summing the surface area of each cell of the elevation raster that falls within a desired probability contour of the 2D MKDE. An algorithm developed by Jenness (2004, 2014) is used to compute the surface area of each raster cell. This method uses the cell center coordinates and elevations of the focal cell and its eight neighboring cells to construct eight triangular facets within the focal cell. The area of each facet is calculated using Heron's formula and then summed to obtain the surface area for the focal cell.

Numerous functions are provided to write output files in various formats (VTK, XDMF, ASCII) for use in other GIS and 3D Visualization applications.

Details

Package:	mkde
Type:	Package
Version:	1.0
Date:	2011-08-23
License:	GPL-2
LazyLoad:	yes

Author(s)

Jeff A. Tracey (US Geological Survey, San Diego Field Station, Western Ecological Research Center)

James Sheppard (San Diego Zoo Institute for Conservation Research)

Jun Zhu (Department of Statistics and Department of Entomology, University of Wisconsin – Madison)

Robert Sinkovits (San Diego Supercomputer Center)

Amit Chourasia (San Diego Supercomputer Center)

Glenn Lockwood (San Diego Supercomputer Center)

Maintainer: Jeff A. Tracey <jatracey@usgs.gov, jeff.a.tracey@gmail.com>

References

- Tracey, J. A., Sheppard, J., Zhu, J., Wei, F., Swaisgood, R. R. and Fisher, R. N. (2014) Movement-Based Estimation and Visualization of Space Use in 3D for Wildlife Ecology and Conservation. PLoS ONE 9(7): e101205. doi: 10.1371/journal.pone.0101205
- Tracy, J. A., Sheppard, J. Lockwood, G., Chourasia, A., Tatineni, M., Fisher, R. N., and Sinkovits, R. (2014) Efficient 3D Movement-Based Kernel Density Estimator and Application to Wildlife Ecology. XSEDE 14 Conference Proceedings, Article No. 14. doi: 10.1145/2616498.2616522
- Belant, J. L., Millsaugh, J. J., Martin, J. A. & Gitzen, R. A. (2012). Multi-dimensional space use: the final frontier. *Frontiers in Ecology & Environment* 10, 11-12.
- Benhamou, S. (2011). Dynamic Approach to Space and Habitat Use Based on biased random bridges. PLoS ONE 6.
- Hansen, M. C., & Riggs, R. A. (2008). Accuracy, precision, and observation rates of global positioning system telemetry collars. *The Journal of Wildlife Management*, 72(2), 518-526.
- Horne, J. S., Garton, E. O., Krone, S. M., Lewis, J. S. (2007). Analyzing animal movements using Brownian bridges. *Ecology* 88, 2354-2363.
- Jenness J. S. (2004) Calculating landscape surface area from digital elevation models. *Wildlife Society Bulletin* 32: 829-839.
- Jenness, J. S. (2014) Calculating landscape surface area from unprojected digital elevation models. In preparation.

computeAreaRaster

Calculate cell areas from elevation raster.

Description

A lower-level function for calculating a cell area matrix (2D array) from an elevation matrix. The area is based on the surface area of the terrain in the cell. The area matrix is then used in calculating areas of 2.5D MKDES.

Usage

```
computeAreaRaster(RelevMatrix, RcellSize)
```

Arguments

RelevMatrix	A 2D array with elevation values.
RcellSize	Size of the cells. It is assumed to be the same in the x and y dimensions.

Details

This is a wrapper function for C++ function that calculates the surface area of each raster cell given the cell elevations. It is not intended to be used directly; instead, the user should call `initializeAreaRaster` on an MKDE object.

Value

A 2D matrix of cell surface areas.

Author(s)

Jeff A. Tracey, PhD
USGS Western Ecological Research Center, San Diego Field Station
<jatracey@usgs.gov>
James Sheppard, PhD
San Diego Zoo Institute for Conservation Research
<jsheppard@sandiegozoo.org>

References

Jenness J.S. (2004) Calculating landscape surface area from digital elevation models. *Wildlife Society Bulletin* 32: 829-839.
Jenness, J.S. (2014) Calculating landscape surface area from unprojected digital elevation models. In preparation.

Examples

```
library(terra)
fpath <- system.file("extdata", "condordem.RDS", package="mkde")
condordem <- terra::readRDS(fpath)
cell.sz <- mean(res(condordem))
area.rast <- computeAreaRaster(as.matrix(condordem, wide=TRUE), cell.sz)
```

computeContourValues *Find thresholds for contour intervals*

Description

Find the cell or voxel probabilities that correspond to user-specified probability contours

Usage

```
computeContourValues(mkde.obj, prob)
```

Arguments

mkde.obj	An MKDE object with density initialized
prob	Probabilities (i.e. proportions) for desired contours of the MKDE

Details

This function computes threshold cell or voxel probability values corresponding to contours for specified proportions of the utilization distribution. Note that the argument prob specifies the cumulative probability of the cells or voxels within the contour corresponding to the cell or voxel threshold probability. The cell or voxel threshold probabilities may be orders of magnitude smaller than the cumulative probabilities provided in the prob argument.

Value

A data frame with the probabilities given in the prob argument and corresponding thresholds in the MKDE

Author(s)

Jeff A. Tracey, PhD
 USGS Western Ecological Research Center, San Diego Field Station
 <jatracey@usgs.gov>
 James Sheppard, PhD
 San Diego Zoo Institute for Conservation Research
 <jsheppard@sandiegozoo.org>

Examples

```
data(condor)

# Find min/max coordinates and add buffer
xmax = max(condor$x) + 1000
xmin = min(condor$x) - 1000
ymax = max(condor$y) + 1000
ymin = min(condor$y) - 1000

# Calculate grid dimensions
xrange <- xmax - xmin
yrange <- ymax - ymin
cell.sz = 150
nx <- as.integer(xrange/cell.sz)
ny <- as.integer(yrange/cell.sz)

mv.dat <- initializeMovementData(condor$t, condor$x, condor$y, sig2obs=25.0, t.max=185.0)
mkde.obj <- initializeMKDE2D(xmin, cell.sz, nx, ymin, cell.sz, ny)
dens.res <- initializeDensity(mkde.obj, mv.dat)

mkde.obj <- dens.res$mkde.obj
mv.dat <- dens.res$move.dat
my.quantiles <- c(0.95, 0.75, 0.50)
res <- computeContourValues(mkde.obj, my.quantiles)
print(res)
```

computeSizeMKDE

Compute the area or volume of an MKDE.

Description

For 2D MKDEs, this function computes the area. For a 2.5D MKDE it computes the area based on the cell areas computed from an elevation raster. For a 3D MKDE, it computes the volume.

Usage

```
computeSizeMKDE(mkde.obj, prob)
```

Arguments

mkde.obj	MKDE list object with density estimate calculated.
prob	Probabilities for the desired contours.

Details

For a 2D or 2.5D MKDE list object, areas within the contours specified by quant are calculated. For a 3D MKDE, the volumes within the contours are calculated.

Value

A vector with the areas or volumes is returned.

Author(s)

Jeff A. Tracey, PhD
 USGS Western Ecological Research Center, San Diego Field Station
 <jatracey@usgs.gov>
 James Sheppard, PhD
 San Diego Zoo Institute for Conservation Research
 <jsheppard@sandiegozoo.org>

Examples

```
library(terra)
data(condor)

condor <- condor[1:20,] # simply to make example run more quickly
mv.dat <- initializeMovementData(condor$time, condor$x, condor$y,
z.obs=condor$z, sig2obs=25.0, sig2obs.z=81.0, t.max=65.0)

fpath <- system.file("extdata", "condordem120.RDS", package="mkde")
condordem120 <- terra::readRDS(fpath)
cell.sz <- mean(res(condordem120))
ext <- ext(condordem120)
nx <- ncol(condordem120)
ny <- nrow(condordem120)
mkde.obj <- initializeMKDE3D(ext$xmin, cell.sz, nx, ext$ymin, cell.sz,
ny, min(values(condordem120), na.rm=TRUE), cell.sz, 25)

# note: we use a raster coarse integration time step so the
# example runs faster
dens.res <- initializeDensity(mkde.obj, mv.dat, integration.step=10.0)
mkde.obj <- dens.res$mkde.obj
mv.dat <- dens.res$move.dat

my.quantiles <- c(0.95, 0.75, 0.50)
```

```
res <- computeContourValues(mkde.obj, my.quantiles)
res$volume <- computeSizeMKDE(mkde.obj, my.quantiles)
print(res)
```

condor

California condor locations

Description

A data frame containing California condor location data

Usage

```
data(condor)
```

Format

A data frame with 421 observations on the following 4 variables.

`time` Elapsed time in minutes
`x` x-coordinate (UTM easting in meters)
`y` y-coordinate (UTM northing in meters)
`z` z-coordinate (height above sea level in meters)

Details

GPS location data acquired from a wild California condor (*Gymnogyps californianus*) tracked by San Diego Zoo Global around its reintroduction site in Baja California, Mexico during November 2012 (Sheppard et al. 2013).

Source

James Sheppard, San Diego Zoo Institute for Conservation Research

References

Sheppard, J.K., Walenski, M., Wallace, M.P., Velazco, J.J.V., Porras, C., & Swaisgood, R.R. (2013). Hierarchical dominance structure in reintroduced California condors: correlates, consequences, and dynamics. *Behavioral Ecology and Sociobiology*. 67: 1-12.

Examples

```
data(condor)
head(condor, 30)
```

`deselectLocationsOutsideBounds`*Flag 3D locations with out-of-bounds z-coordinates*

Description

For a 3D MKDE object and 3D location data, the z-coordinates in the location data are checked to make sure they are within the lower and upper bounds specified in the MKDE list object.

Usage

```
deselectLocationsOutsideBounds(move.dat, mkde.obj)
```

Arguments

<code>move.dat</code>	A move data object created with <code>initializeMovementData</code>
<code>mkde.obj</code>	An MKDE object created with <code>initialize2DMKDE</code> or <code>initialize3DMKDE</code>

Details

If a 2D or 2.5D MDKE object is passed as an argument, no change is made to the movement data list object. If a 3D MKDE list object is passed as an argument, the z-coordinates in the movement data are checked to determine if they are in range. If they are not, the corresponding value in `move.dat$use.obs` is set to `FALSE`. Note that this function is not called within `initializeDensity`. If you want to exclude locations because they are outside of the allowed range in the z-dimension, this function must be used before computing the density.

Value

An updated move data list object is returned.

Author(s)

Jeff A. Tracey, PhD
USGS Western Ecological Research Center, San Diego Field Station
<jatracey@usgs.gov>
James Sheppard, PhD
San Diego Zoo Institute for Conservation Research
<jsheppard@sandiegozoo.org>

Examples

```
library(terra)
data(condor)
mv.dat <- initializeMovementData(condor$time, condor$x, condor$y,
z.obs=condor$z, sig2obs=25.0, sig2obs.z=81.0, t.max=65.0)

fpath <- system.file("extdata", "condordem.RDS", package="mkde")
```

```
condordem <- terra::readRDS(fpath)

cell.sz <- mean(res(condordem))
ext <- ext(condordem)
nx <- ncol(condordem)
ny <- nrow(condordem)
mkde.obj <- initializeMKDE3D(ext$xmin, cell.sz, nx, ext$ymin, cell.sz,
ny, min(values(condordem), na.rm=TRUE), 30.0, 100)
mkde.obj <- setMinimumZfromRaster(mkde.obj, condordem)
mv.dat <- deselectLocationsOutsideBounds(mv.dat, mkde.obj)
```

deselectNonMovementSteps

Flag non-movements so they are excluded from MKDE estimation

Description

This function deselects move steps where the probability that the initial and final location are the same location is greater than or equal to a user-defined threshold probability

Usage

```
deselectNonMovementSteps(move.dat, p)
```

Arguments

move.dat	A move data object created with <code>initializeMovementData</code>
p	The threshold probability

Details

If the probability that the initial and final location are the same location is greater than or equal to a user-defined threshold probability, the corresponding value in `move.dat$use.obs` is set to `FALSE`. Note that this function is not called within `initializeDensity`. If you want to exclude locations because they the initial location in a non-movement step, this function must be used before computing the density.

Value

An updated move data list object is returned.

Author(s)

Jeff A. Tracey, PhD
USGS Western Ecological Research Center, San Diego Field Station
<jatracey@usgs.gov>
James Sheppard, PhD
San Diego Zoo Institute for Conservation Research
<jsheppard@sandiegozoo.org>

Examples

```
data(condor)
mv.dat <- initializeMovementData(condor$time, condor$x, condor$y,
z.obs=condor$z, sig2obs=25.0, sig2obs.z=81.0, t.max=65.0)

mv.dat <- deselectNonMovementSteps(mv.dat, 0.05)
```

dugong

Dugong locations

Description

A data frame containing dugong location data

Usage

```
data(dugong)
```

Format

A data frame with 426 observations on the following 4 variables.

time Elapsed time in minutes
x x-coordinate (UTM easting in meters)
y y-coordinate (UTM northing in meters)
z z-coordinate (Depth in meters)

Details

GPS location data acquired from a wild dugong (*Dugong dugon*) tracked by James Cook University in Hervey Bay, Australia during August 2004 (Sheppard et. al. 2010)

Source

James Sheppard, San Diego Zoo Institute for Conservation Research

References

Sheppard, J. Marsh, H., Jones, R.E., & Lawler, I.R. (2010). Dugong habitat use in relation to seagrass nutrients, tides, and diel cycles. *Marine Mammal Science* 26, 855-879.

Examples

```
data(dugong)
head(dugong, 30)
```

`estVarMKDE`*Estimate move variances for 3D MKDE.*

Description

Estimates the move variance for the (x, y) and z dimensions and altitude for a Brownian bridge MKDE.

Usage

```
estVarMKDE(move.dat)
```

Arguments

`move.dat` A move data object created with `initializeMovementData`

Details

Computes maximum-likelihood estimates for move variances. If the MKDE is 2D or 2.5D, only the variance for the xy-dimension is estimated. If the MKDE is 3D, a separate move variance for the z-dimension is also estimated.

Value

A move data object updated with move variances

Author(s)

Jeff A. Tracey, PhD
USGS Western Ecological Research Center, San Diego Field Station
<jatracey@usgs.gov>
James Sheppard, PhD
San Diego Zoo Institute for Conservation Research
<jsheppard@sandiegozoo.org>

Examples

```
data(condor)
mv.dat <- initializeMovementData(condor$time, condor$x, condor$y,
z.obs=condor$z, sig2obs=25.0, sig2obs.z=81.0, t.max=65.0)

mv.dat <- estVarMKDE(mv.dat)
cat(paste("Move variance in xy-dimensions = ",
mv.dat$sig2xy[1], "\n", sep=""))
cat(paste("Move variance in z-dimension = ",
mv.dat$sig2z[1], "\n", sep=""))
```

initializeAreaRaster *Initialize an area raster for a 2.5D MKDE.*

Description

Initialize the surface area for a 2.5D MKDE.

Usage

```
initializeAreaRaster(mkde.obj)
```

Arguments

mkde.obj An MKDE object created using initialize2DMKDE

Details

After creating the MKDE object and setting the lower bounds in the z-dimension using setMinimumZfromRaster, this function computes the surface area of each raster cell and sets the dimension of the MKDE object to 2.5.

Value

Returns a 2.5 MKDE object with an initialized area raster.

Author(s)

Jeff A. Tracey, PhD
USGS Western Ecological Research Center, San Diego Field Station
<jatracey@usgs.gov>
James Sheppard, PhD
San Diego Zoo Institute for Conservation Research
<jsheppard@sandiegozoo.org>

Examples

```
library(terra)
fpath <- system.file("extdata", "pandadem.RDS", package="mkde")
pandadem <- terra::readRDS(fpath)
cell.sz <- mean(res(pandadem))
ext <- ext(pandadem)
nx <- ncol(pandadem)
ny <- nrow(pandadem)
mkde.obj <- initializeMKDE2D(ext$xmin, cell.sz, nx, ext$ymin, cell.sz, ny)

mkde.obj <- setMinimumZfromRaster(mkde.obj, pandadem)
mkde.obj <- initializeAreaRaster(mkde.obj)
```

initializeDensity *Calculate raster of density values for MKDE.*

Description

Given a movement data object (list) and MKDE object (list), estimate the movement variance parameters and update them in the movement data object and then compute the density for a 2D, 2.5D, or 3D MKDE.

Usage

```
initializeDensity(mkde.obj, move.dat, integration.step, d.thresh=1e-25)
```

Arguments

mkde.obj	An MKDE object created with initialize2DMKDE or initialize3DMKDE
move.dat	A move data object created with initializeMovementData
integration.step	A time step used for numerical integration over the movement trajectory
d.thresh	The value of the kernel below which its contribution to the overall density is considered negligible

Details

This function computes the density for a 2D, 2.5D, or 3D MKDE. If the move variance parameters have not been estimated, they will be prior to computing the density. The integration time step should be much less than the maximum time step allowed between observed animal locations. For a 2.5D MKDE, if the area has been calculated with initializeAreaRaster, then the cell probabilities are weighted by the proportion of the total surface area represented by the cell.

Value

A list is returned with two elements: move.dat and mkde.obj. The first is an updated move data object and the second is an updated MKDE object.

Author(s)

Jeff A. Tracey, PhD
 USGS Western Ecological Research Center, San Diego Field Station
 <jatracey@usgs.gov>
 James Sheppard, PhD
 San Diego Zoo Institute for Conservation Research
 <jsheppard@sandiegozoo.org>
 Robert Sinkovits, PhD
 San Diego Supercomputer Center
 <sinkovit@sdsc.edu >
 Glenn Lockwood, PhD

San Diego Supercomputer Center
<glock@sdsc.edu>

Examples

```
library(terra)
data(condor)
condor <- condor[1:20,] # simply to make example run more quickly
mv.dat <- initializeMovementData(condor$time, condor$x, condor$y,
z.obs=condor$z, sig2obs=25.0, sig2obs.z=81.0, t.max=65.0)

fpath <- system.file("extdata", "condordem120.RDS", package="mkde")
condordem120 <- terra::readRDS(fpath)
cell.sz <- mean(res(condordem120))
ext <- ext(condordem120)
nx <- ncol(condordem120)
ny <- nrow(condordem120)
mkde.obj <- initializeMKDE3D(ext$xmin, cell.sz, nx, ext$ymin, cell.sz,
ny, min(values(condordem120), na.rm=TRUE), cell.sz, 25)

# note: we use a raster coarse integration time step so the
# example runs faster
dens.res <- initializeDensity(mkde.obj, mv.dat, integration.step=10.0)
mkde.obj <- dens.res$mkde.obj
mv.dat <- dens.res$move.dat
```

initializeMKDE2D *Set up a 2D MKDE object.*

Description

Define the spatial extent and resolution of a 2D MKDE and create an 2D MKDE list object for use in other functions in the package.

Usage

```
initializeMKDE2D(xLL, xCellSize, nX, yLL, yCellSize, nY)
```

Arguments

xLL	Lower bounds of the grid in the x-dimension
xCellSize	Cell size in the x-dimension
nX	Number of cells in the x-dimension
yLL	Lower bounds of the grid in the y-dimension
yCellSize	Cell size in the y-dimension
nY	Number of cells in the y-dimension

Details

It is strongly recommended that the same value is used for `xCellSize` and `yCellSize`. The grid should be defined so that it covers the area that the animal used, plus a sufficient buffer so that the density is negligible beyond the grid.

Value

A list representing an MKDE object is returned with the following elements:

<code>dimension</code>	The dimension of the MKDE; that is, 2.
<code>x</code>	A grid of points along the x-axis where the cell centers occur.
<code>y</code>	A grid of points along the y-axis where the cell centers occur.
<code>z</code>	A grid of points along the z-axis where the cell centers occur. For a 2D MKDE <code>z = NA</code> .
<code>z.min</code>	A 2D array representing the lower bounds of space in the z-dimension at each x and y coordinate. Defaults to <code>-Inf</code> .
<code>z.max</code>	A 2D array representing the upper bounds of space in the z-dimension at each x and y coordinate. Defaults to <code>Inf</code> .
<code>nx</code>	Number of cells in the x-dimension.
<code>ny</code>	Number of cells in the y-dimension.
<code>nz</code>	Number of cells in the z-dimension. For a 2D MKDE <code>nz = 1</code> .
<code>d</code>	A 2D array with dimensions <code>(nx, ny)</code> that stores the density. The elements are initialized to <code>NA</code> .

Author(s)

Jeff A. Tracey, PhD
 USGS Western Ecological Research Center, San Diego Field Station
jatracey@usgs.gov
 James Sheppard, PhD
 San Diego Zoo Institute for Conservation Research
jsheppard@sandiegozoo.org

Examples

```
library(terra)
fpath <- system.file("extdata", "pandadem.RDS", package="mkde")
pandadem <- terra::readRDS(fpath)
cell.sz <- mean(res(pandadem))
ext <- ext(pandadem)
nx <- ncol(pandadem)
ny <- nrow(pandadem)
mkde.obj <- initializeMKDE2D(ext$xmin, cell.sz, nx, ext$ymin, cell.sz, ny)
```

initializeMKDE3D	<i>Set up a 3D MKDE object.</i>
------------------	---------------------------------

Description

Define the spatial extent and resolution of a 3D MKDE and create an 3D MKDE list object for use in other functions in the package.

Usage

```
initializeMKDE3D(xLL, xCellSize, nX, yLL, yCellSize, nY,
zLL, zCellSize, nZ)
```

Arguments

xLL	Lower bounds of the grid in the x-dimension
xCellSize	Cell size in the x-dimension
nX	Number of cells in the x-dimension
yLL	Lower bounds of the grid in the y-dimension
yCellSize	Cell size in the y-dimension
nY	Number of cells in the y-dimension
zLL	Lower bounds of the grid in the z-dimension
zCellSize	Cell size in the z-dimension
nZ	Number of cells in the z-dimension

Details

It is strongly recommended that the same value is used for xCellSize and yCellSize. The grid should be defined so that it covers the volume that the animal used, plus a sufficient buffer so that the density is negligible beyond the grid.

Value

A list representing an MKDE object is returned with the following elements:

dimension	The dimension of the MKDE; that is, 3.
x	A grid of points along the x-axis where the voxel centers occur.
y	A grid of points along the y-axis where the voxel centers occur.
z	A grid of points along the z-axis where the voxel centers occur.
z.min	A 2D array representing the lower bounds of space in the z-dimension at each x and y coordinate. Defaults to a constant value based on the arguments zLL, zCellSize, and nZ.

z.max	A 2D array representing the upper bounds of space in the z-dimension at each x and y coordinate. Defaults to a constant value based on the arguments zLL, zCellSize, and nZ.
nx	Number of cells in the x-dimension.
ny	Number of cells in the y-dimension.
nz	Number of cells in the z-dimension.
d	A 3D array with dimensions (nx, ny, nz) that stores the density. The elements are initialized to NA.

Author(s)

Jeff A. Tracey, PhD
 USGS Western Ecological Research Center, San Diego Field Station
 <jatracey@usgs.gov>
 James Sheppard, PhD
 San Diego Zoo Institute for Conservation Research
 <jsheppard@sandiegozoo.org>

Examples

```
library(terra)
fpath <- system.file("extdata", "condordem.RDS", package="mkde")
condordem <- terra::readRDS(fpath)
cell.sz <- mean(res(condordem))
ext <- ext(condordem)
nx <- ncol(condordem)
ny <- nrow(condordem)
zmin <- min(values(condordem), na.rm=TRUE)
nz <- 30
mkde.obj <- initializeMKDE3D(ext$xmin, cell.sz, nx, ext$ymin, cell.sz,
ny, zmin, cell.sz, nz)
```

```
initializeMovementData
```

Initialize a movement data list

Description

This function sets up the movement data for use in other functions in the package.

Usage

```
initializeMovementData(t.obs, x.obs, y.obs, z.obs=NULL, sig2obs=0.0,
sig2obs.z=NA, t.max=max(diff(t.obs), na.rm=TRUE))
```

Arguments

t.obs	A vector of times at which the animal locations were observed
x.obs	A vector of x-coordinates at which the animal locations were observed
y.obs	A vector of y-coordinates at which the animal locations were observed
z.obs	A vector of z-coordinates at which the animal locations were observed
sig2obs	Location error variance in the xy-dimensions
sig2obs.z	Location error variance in the z-dimension
t.max	The maximum time allowed between locations if the movement step is to be used in computing the density

Details

If only 2D or 2.5D MKDEs are to be calculated, then z.obs and sig2obs.z do not have to be provided.

Value

A move data object, in the form of a list, is returned.

dimension	The spatial dimension of the movement data. If z-coordinates are passed, the dimension will be 3; otherwise, the dimension will be 2.
t.obs	Times of the animal locations.
x.obs	x-coordinates of the animal locations.
y.obs	y-coordinates of the animal locations.
z.obs	z-coordinates of the animal locations.
a.obs	Altitude of the animal; that is, its z-coordinate minus the lower bound on the z-coordinate at the corresponding xy-coordinates of the animal location.
use.obs	A logical array that indicates whether each location should be used in the MKDE calculations. By default these values are set to TRUE.
t.max	The maximum time allowed between locations if the movement step is to be used in computing the density
sig2xy	A vector of movement variance parameters for the xy-dimensions, with NAs as placeholders. The function estVarMKDE is provided to estimate these parameters, or they can be set manually to allow for different movement variances for each move step.
sig2z	A vector of movement variance parameters for the z-dimension, with NAs as placeholders. The function estVarMKDE is provided to estimate these parameters, or they can be set manually to allow for different movement variances for each move step.
sig2obs	A vector of variances for the location observation error in the xy-dimensions. If only one value is provided for the variance parameters, the value is repeated to form a vector with one element for each location. Otherwise, a vector of location error variances can be passed to allow for different errors for each observed location.

`sig2obs.z` A vector of variances for the location observation error in the z-dimension. If only one value is provided for the variance parameters, the value is repeated to form a vector with one element for each location. Otherwise, a vector of location error variances can be passed to allow for different errors for each observed location.

Author(s)

Jeff A. Tracey, PhD
 USGS Western Ecological Research Center, San Diego Field Station
 <jatracey@usgs.gov>
 James Sheppard, PhD
 San Diego Zoo Institute for Conservation Research
 <jsheppard@sandiegozoo.org>

Examples

```
data(condor)
mv.dat <- initializeMovementData(condor$time, condor$x,
condor$y, z.obs=condor$z, 65.0, 25.0, sig2obs.z=81.0)
```

mkde2Dgrid

Movement-based kernel density estimate (MKDE) in 2D using Rcpp

Description

Provides a function for 2-dimensional MKDEs.

Usage

```
mkde2Dgrid(mkde.obj, move.dat, t.step, d.thresh)
```

Arguments

<code>mkde.obj</code>	A 2D or 2.5D MKDE object
<code>move.dat</code>	A move data object
<code>t.step</code>	An integration time step
<code>d.thresh</code>	A kernel density threshold

Details

This is lower-level function that call the C++ function. for estimating the movement-based density in 2D. In practice, users should call `initializeDensity`.

The argument `d.thresh` is a univariate probability density beyond which the kernel contribution to the overall MKDE is assumed to be negligible. Usually this is set at a very small value and is used to prevent calculations from being performed in cells to which the kernel makes a negligible contribution.

Value

An array whose elements are the estimated utilization probabilities for each cell.

Author(s)

Jeff A. Tracey, PhD
USGS Western Ecological Research Center, San Diego Field Station
<jatracey@usgs.gov>
James Sheppard, PhD
San Diego Zoo Institute for Conservation Research
<jsheppard@sandiegozoo.org>
Robert Sinkovits, PhD
San Diego Supercomputer Center
<sinkovit@sdsc.edu >
Glenn Lockwood, PhD
San Diego Supercomputer Center
<glock@sdsc.edu>
Jun Zhu, PhD
University of Wisconsin-Madison
<jzhu@stat.wisc.edu>

Examples

```
data(panda)

# Find min/max coordinates and add buffer
xmax = max(panda$x) + 100
xmin = min(panda$x) - 100
ymax = max(panda$y) + 100
ymin = min(panda$y) - 100

# Calculate grid dimensions
xrange <- xmax - xmin
yrange <- ymax - ymin
cell.sz = 30
nx <- as.integer(xrange/cell.sz)
ny <- as.integer(yrange/cell.sz)

mv.dat <- initializeMovementData(panda$time, panda$x, panda$y, t.max=185.0, sig2obs=25.0)
if (all(is.na(mv.dat$sig2xy))) {
  mv.dat <- estVarMKDE(mv.dat)
}

mkde.obj <- initializeMKDE2D(xmin, cell.sz, nx, ymin, cell.sz, ny)
res <- mkde2Dgrid(mkde.obj, mv.dat, 10.0, 1e-20)
```

mkde2Dinteraction *Probability of 2D spatial-temporal interaction.*

Description

Probability of 2D spatial-temporal interaction.

Usage

```
mkde2Dinteraction(mkde.obj, move.dat0, move.dat1, t.step, d.thresh)
```

Arguments

mkde.obj	An MKDE object created with <code>initialize2DMKDE</code>
move.dat0	A move data object for the first individual created with <code>initializeMovementData</code>
move.dat1	A move data object for the second individual created with <code>initializeMovementData</code>
t.step	A time step used for numerical integration over the movement trajectory
d.thresh	The value of the kernel below which its contribution to the overall density is considered negligible

Details

This function assumes that the two individual animals were observed at the same times. The cell values returned in the `mkde.obj` can be summed to obtain a global measure of spatio-temporal interaction.

Value

Returns a list with the following elements:

mkde.obj	An updated MKDE object containing the cell-level Bhattacharyya coefficients
move.dat0	A move data object for the first individuals with updated variance parameters
move.dat1	A move data object for the second individuals with updated variance parameters

Author(s)

Jeff A. Tracey, PhD
 USGS Western Ecological Research Center, San Diego Field Station
 <jatracey@usgs.gov>
 James Sheppard, PhD
 San Diego Zoo Institute for Conservation Research
 <jsheppard@sandiegozoo.org>
 Jun Zhu, PhD
 University of Wisconsin-Madison
 <jzhu@stat.wisc.edu>

Examples

```
library(terra)
data(panda)
mv.dat0 <- initializeMovementData(panda$time, panda$x, panda$y,
  sig2obs=25.0, t.max=185.0)

n <- nrow(panda)
v <- 20.0 # increase from 0 to increase difference
mv.dat1 <- initializeMovementData(panda$time, panda$x+rnorm(n, 0, v),
  panda$y+rnorm(n, 0, v), sig2obs=25.0, t.max=185.0)

fpath <- system.file("extdata", "pandadem.RDS", package="mkde")
pandadem <- terra::readRDS(fpath)
cell.sz <- mean(res(pandadem))
ext <- ext(pandadem)
nx <- ncol(pandadem)
ny <- nrow(pandadem)
mkde.obj <- initializeMKDE2D(ext$xmin, cell.sz, nx, ext$ymin, cell.sz,
  ny)

res <- mkde2Dinteraction(mkde.obj, mv.dat0, mv.dat1, 10.0, 1e-20)
mkde.obj <- res$mkde.obj
mv.dat0 <- res$move.dat0
mv.dat1 <- res$move.dat1
```

mkde3Dgrid

Movement-based kernel density estimate (MKDE) in 3D using Rcpp

Description

Provides a function for 3-dimensional MKDEs.

Usage

```
mkde3Dgrid(mkde.obj, move.dat, t.step, d.thresh)
```

Arguments

mkde.obj	A 3D MKDE object
move.dat	A move data object
t.step	An integration time step
d.thresh	A kernel density threshold

Details

This is lower-level function that call the C++ function. for estimating the movement-based density in 3D. In practice, users should call `initializeDensity`.

The argument `d.thresh` is a univariate probability density beyond which the kernel contribution to the overall MKDE is assumed to be negligible. Usually this is set at a very small value and is used to prevent calculations from being performed in cells to which the kernel makes a negligible contribution.

Value

An array whose elements are the estimated utilization probabilities for each voxel.

Author(s)

Jeff A. Tracey, PhD
 USGS Western Ecological Research Center, San Diego Field Station
 <jatracey@usgs.gov>
 James Sheppard, PhD
 San Diego Zoo Institute for Conservation Research
 <jsheppard@sandiegozoo.org>
 Robert Sinkovits, PhD
 San Diego Supercomputer Center
 <sinkovit@sdsc.edu >
 Glenn Lockwood, PhD
 San Diego Supercomputer Center
 <glock@sdsc.edu>
 Jun Zhu, PhD
 University of Wisconsin-Madison
 <jzhu@stat.wisc.edu>

Examples

```
data(condor)

# Find min/max coordinates and add buffer
xmax = max(condor$x) + 1000
xmin = min(condor$x) - 1000
ymax = max(condor$y) + 1000
ymin = min(condor$y) - 1000

# Calculate grid dimensions
xrange <- xmax - xmin
yrange <- ymax - ymin
cell.sz = 600
nx <- as.integer(xrange/cell.sz)
ny <- as.integer(yrange/cell.sz)
nz <- ceiling(3000.0/cell.sz)

mv.dat <- initializeMovementData(condor$time, condor$x, condor$y, z.obs=condor$z, t.max=185.0,
sig2obs=25.0, sig2obs.z=81.0)
```



```

if (all(is.na(mv.dat$sig2xy))) {
  mv.dat <- estVarMKDE(mv.dat)
}

mkde.obj <- initializeMKDE3D(xmin, cell.sz, nx, ymin, cell.sz, ny, 0.0, cell.sz, nz)
res <- mkde3Dgrid(mkde.obj, mv.dat, 5.0, 1e-20)

```

mkde3Dinteraction *Probability of 3D spatial-temporal interaction.*

Description

Metric of 3D spatial-temporal interaction.

Usage

```
mkde3Dinteraction(mkde.obj, move.dat0, move.dat1, t.step, d.thresh)
```

Arguments

mkde.obj	An MKDE object created with <code>initialize3DMKDE</code>
move.dat0	A move data object for the first individual created with <code>initializeMovementData</code>
move.dat1	A move data object for the second individual created with <code>initializeMovementData</code>
t.step	A time step used for numerical integration over the movement trajectory
d.thresh	The value of the kernel below which its contribution to the overall density is considered negligible

Details

This function assumes that the two individual animals were observed at the same times. The voxel values returned in the `mkde.obj` can be summed to obtain a global measure of spatio-temporal interaction.

Value

Returns a list with the following elements:

mkde.obj	An updated MKDE object containing the voxel-level Bhattacharyya coefficients
move.dat0	A move data object for the first individuals with updated variance parameters
move.dat1	A move data object for the second individuals with updated variance parameters

Author(s)

Jeff A. Tracey, PhD
 USGS Western Ecological Research Center, San Diego Field Station
 <jatracey@usgs.gov>
 James Sheppard, PhD
 San Diego Zoo Institute for Conservation Research
 <jsheppard@sandiegozoo.org>
 Jun Zhu, PhD
 University of Wisconsin-Madison
 <jzhu@stat.wisc.edu>

Examples

```
library(terra)
data(condor)
condor <- condor[1:4,] # simply to make example run more quickly
mv.dat0 <- initializeMovementData(condor$time, condor$x, condor$y,
  z.obs=condor$z, sig2obs=25.0, sig2obs.z=81.0, t.max=65.0)
n <- nrow(condor)
v <- 20.0 # increase from 0 to increase difference between move trajectories
vz <- 5.0
mv.dat1 <- initializeMovementData(condor$time, condor$x+rnorm(n, 0, v),
  condor$y+rnorm(n, 0, v), z.obs=condor$z+rnorm(n, 0, vz), sig2obs=25.0,
  sig2obs.z=81.0, t.max=65.0)

fpath <- system.file("extdata", "condordem120.RDS", package="mkde")
condordem120 <- terra::readRDS(fpath)
# next two lines reduce extent of 2D space to speed execution of example
tmp <- ext(c(range(condor$x) + c(-100, 100), range(condor$y) + c(-100, 100)))
condordem120 <- crop(condordem120, tmp)
cell.sz <- mean(res(condordem120))
ext <- ext(condordem120)
nx <- ncol(condordem120)
ny <- nrow(condordem120)
nz <- ceiling(3000.0/cell.sz)
mkde.obj <- initializeMKDE3D(ext$xmin, cell.sz, nx, ext$ymin, cell.sz,
  ny, 0.0, cell.sz, nz)

res <- mkde3Dinteraction(mkde.obj, mv.dat0, mv.dat1, 10.0, 1e-20)
mkde.obj <- res$mkde.obj
mv.dat0 <- res$move.dat0
mv.dat1 <- res$move.dat1
```

mkdeToRaster

MKDE to RasterLayer or RasterStack

Description

Converts an MKDE into a RasterLayer or RasterStack so that raster package functions can be used.

Usage

```
mkdeToRaster(mkde.obj)
```

Arguments

mkde.obj A 2D, 2.5D, or 3D MKDE object created with `initialize2DMKDE` or `initialize3DMKDE` and density initialized with `initializeDensity`

Details

This method converts the density array in the MKDE object to an object of a class from the raster package. This allows the functions in the raster package to be used with the MKDEs.

Value

If the MKDE is 2D or 2.5D, a RasterLayer object is returned. If the MKDE is 3D, a RasterStack is returned with one layer in the stack per level.

Author(s)

Jeff A. Tracey, PhD
 USGS Western Ecological Research Center, San Diego Field Station
 <jatracey@usgs.gov>
 James Sheppard, PhD
 San Diego Zoo Institute for Conservation Research
 <jsheppard@sandiegozoo.org>

Examples

```
library(terra)

# set up MKDE object
fpath <- system.file("extdata", "pandadem.RDS", package="mkde")
pandadem <- terra::readRDS(fpath)
cell.sz <- mean(res(pandadem))
ext <- ext(pandadem)
nx <- ncol(pandadem)
ny <- nrow(pandadem)
mkde.obj <- initializeMKDE2D(ext$xmin, cell.sz, nx, ext$ymin, cell.sz, ny)

# set up movement data
data(panda)
mv.dat <- initializeMovementData(panda$time, panda$x, panda$y,
  sig2obs=25.0, t.max=185.0)

# estimate density
dens.res <- initializeDensity(mkde.obj, mv.dat)
mkde.obj <- dens.res$mkde.obj
mv.dat <- dens.res$move.dat
mkde.rst <- mkdeToRaster(mkde.obj)
plot(mkde.rst)
```

panda

Giant panda locations

Description

A data frame containing giant panda location data

Usage

```
data(panda)
```

Format

A data frame with 147 observations on the following 4 variables.

time Elapsed time in minutes
x x-coordinate (UTM easting in meters)
y y-coordinate (UTM northing in meters)
z z-coordinate (height above sea level in meters)

Details

GPS location data acquired from a wild giant panda (*Ailuropoda melanoleuca*) tracked by the Chinese Academy of Sciences and San Diego Zoo Global in Foping National Nature Reserve, China during August 2008 (Zhang et. al. 2012).

Source

Giant panda (*Ailuropoda melanoleuca*) biotelemetry data was collected by Fuwen Wei and others of the Key Laboratory of Animal Ecology and Conservation Biology, Institute of Zoology, Chinese Academy of Science, People's Republic of China in collaboration with the San Diego Zoo Institute for Conservation Research. Giant panda research was funded by the National Natural Science Foundation of China (31230011), Wildlife Experimental Platform of Chinese Academy of Sciences, and San Diego Zoo Global.

References

Zhang, Z., Sheppard, J.K., Swaisgood, R.R., Wang, G., Nie, Y., Wei, W., Zhao, N. & Wei, F. (2014). Ecological Scale and Seasonal Heterogeneity in the Spatial Behaviors of Giant Pandas. *Integrative Zoology*, 9: 46-60.

Examples

```
data(panda)  
head(panda, 30)
```

plotMKDE *Make an image plot of an MKDE.*

Description

Makes an image plot of an MKDE. If the MKDE is 3D, the contours will be based on the entire MKDE, but only one level indexed by `z.index` will be plotted.

Usage

```
plotMKDE(mkde.obj, z.index=1, probs=c(0.99, 0.95, 0.90, 0.75, 0.5, 0.0),
cmap=rev(rainbow(length(probs)-1)), add=FALSE, ...)
```

Arguments

<code>mkde.obj</code>	A 2D, 2.5D, or 3D MKDE object created with <code>initialize2DMKDE</code> or <code>initialize3DMKDE</code> and density initialized with <code>initializeDensity</code>
<code>z.index</code>	Index for the z-dimension of the density if a 3D MKDE
<code>probs</code>	Probabilities for image contours.
<code>cmap</code>	Color map for image plot.
<code>add</code>	FALSE to make a new plot, TRUE to add to existing plot
<code>...</code>	Additional graphical parameters.

Details

A plot of the density for the specified level in the z-dimension (which should be 1, the default value, for a 2D or 2.5D MKDE) is generated.

Value

No value is returned.

Author(s)

Jeff A. Tracey, PhD
USGS Western Ecological Research Center, San Diego Field Station
<jatracey@usgs.gov>
James Sheppard, PhD
San Diego Zoo Institute for Conservation Research
<jsheppard@sandiegozoo.org>

Examples

```
library(terra)
fpath <- system.file("extdata", "pandadem.RDS", package="mkde")
pandadem <- terra::readRDS(fpath)
cell.sz <- 0.25*mean(res(pandadem))
ext <- ext(pandadem)
nx <- 4*ncol(pandadem)
ny <- 4*nrow(pandadem)
mkde.obj <- initializeMKDE2D(ext$xmin, cell.sz, nx, ext$ymin, cell.sz, ny)

# set up movement data
data(panda)
mv.dat <- initializeMovementData(panda$time, panda$x, panda$y,
  sig2obs=25.0, t.max=185.0)

# estimate density
dens.res <- initializeDensity(mkde.obj, mv.dat)
mkde.obj <- dens.res$mkde.obj
mv.dat <- dens.res$move.dat
plotMKDE(mkde.obj)
```

readdem_example

Read digital elevation model (DEM) data sets

Description

mkde comes bundled with some example digital elevation model (DEM) data files in its `inst/extdata` directory. This function make them easy to access.

Usage

```
readdem_example(demfile = NULL)
```

Arguments

demfile Name of file. If NULL, the example files will be listed.

Examples

```
readdem_example()
condordem <- readdem_example("condordem.RDS")
condordem120 <- readdem_example("condordem120.RDS")
dugongdem <- readdem_example("dugongdem.RDS")
pandadem <- readdem_example("pandadem.RDS")
```

`setMaximumZfromConstant`*Initialize maximum allowable z-axis coordinates to a constant value.*

Description

Set the upper bounds in the z-dimension for each location in the x and y dimensions to a constant value.

Usage

```
setMaximumZfromConstant(mkde.obj, val)
```

Arguments

<code>mkde.obj</code>	2D or 3D MKDE object created with <code>initialize3DMKDE</code> or <code>initialize3DMKDE</code> , respectively
<code>val</code>	The value at which the upper bound should be set for all locations in the x and y dimensions.

Details

Obviously, the upper bound must be greater than the lower bound.

Value

An updated MKDE list object is returned.

Author(s)

Jeff A. Tracey, PhD
USGS Western Ecological Research Center, San Diego Field Station
<jatracey@usgs.gov>
James Sheppard, PhD
San Diego Zoo Institute for Conservation Research
<jsheppard@sandiegozoo.org>

Examples

```
library(terra)
fpath <- system.file("extdata", "dugongdem.RDS", package="mkde")
dugongdem <- terra::readRDS(fpath)
cell.sz <- mean(res(dugongdem))
ext <- ext(dugongdem)
nx <- ncol(dugongdem)
ny <- nrow(dugongdem)
mkde.obj <- initializeMKDE3D(ext$xmin, cell.sz, nx, ext$ymin, cell.sz,
ny, min(values(dugongdem), na.rm=TRUE), 50.0, 15)
mkde.obj <- setMaximumZfromConstant(mkde.obj, 100.0)
```

setMaximumZfromRaster *Initialize maximum z-axis value from a raster*

Description

Set the upper bounds in the z-dimension for each location in the x and y dimensions from a raster.

Usage

```
setMaximumZfromRaster(mkde.obj, spat.raster)
```

Arguments

mkde.obj	2D or 3D MKDE object created with initialize3DMKDE or initialize3DMKDE, respectively
spat.raster	A RasterLayer object representing the lower bounds of the space the animal may occupy in the z-dimension.

Details

This function sets the upper bounds of the space the animal may occupy in the z-dimension. For example, the `ascii.raster.filez` argument may represent a raster for elevation for subterranean animals, or other surface.

Value

An updated MKDE list object is returned.

Author(s)

Jeff A. Tracey, PhD
USGS Western Ecological Research Center, San Diego Field Station
<jatracey@usgs.gov>
James Sheppard, PhD
San Diego Zoo Institute for Conservation Research
<jsheppard@sandiegozoo.org>

Examples

```
library(terra)
fpath <- system.file("extdata", "dugongdem.RDS", package="mkde")
dugongdem <- terra::readRDS(fpath)
cell.sz <- mean(res(dugongdem))
ext <- ext(dugongdem)
nx <- ncol(dugongdem)
ny <- nrow(dugongdem)
mkde.obj <- initializeMKDE3D(ext$xmin, cell.sz, nx, ext$ymin, cell.sz,
ny, min(values(dugongdem), na.rm=TRUE), 50.0, 15)
mkde.obj <- setMaximumZfromRaster(mkde.obj, dugongdem)
```

`setMinimumZfromConstant`*Set minimum z-axis value to a constant.*

Description

Set the lower bounds in the z-dimension for each location in the x and y dimensions to a constant value.

Usage

```
setMinimumZfromConstant(mkde.obj, val)
```

Arguments

<code>mkde.obj</code>	2D or 3D MKDE object created with <code>initialize3DMKDE</code> or <code>initialize3DMKDE</code> , respectively
<code>val</code>	The value at which the lower bound should be set for all locations in the x and y dimensions.

Details

Obviously, the lower bound must be less than the upper bound.

Value

An updated MKDE list object is returned.

Author(s)

Jeff A. Tracey, PhD
USGS Western Ecological Research Center, San Diego Field Station
<jatracey@usgs.gov>
James Sheppard, PhD
San Diego Zoo Institute for Conservation Research
<jsheppard@sandiegozoo.org>

Examples

```
library(terra)
fpath <- system.file("extdata", "dugongdem.RDS", package="mkde")
dugongdem <- terra::readRDS(fpath)
cell.sz <- mean(res(dugongdem))
ext <- ext(dugongdem)
nx <- ncol(dugongdem)
ny <- nrow(dugongdem)
mkde.obj <- initializeMKDE3D(ext$xmin, cell.sz, nx, ext$ymin, cell.sz,
ny, min(values(dugongdem), na.rm=TRUE), 50.0, 15)
mkde.obj <- setMinimumZfromConstant(mkde.obj, -20.0)
```

setMinimumZfromRaster *Set minimum z-axis values from a raster*

Description

Set the lower bounds in the z-dimension for each location in the x and y dimensions from a raster.

Usage

```
setMinimumZfromRaster(mkde.obj, spat.raster)
```

Arguments

mkde.obj	A 2D or 3D MKDE object created with initialize3DMKDE or initialize3DMKDE, respectively
spat.raster	A RasterLayer object representing the lower bounds of the space the animal may occupy in the z-dimension.

Details

This function sets the lower bounds of the space the animal may occupy in the z-dimension. For example, the `ascii.raster.file` argument may represent a raster for elevation, depth of the sea floor, or other surface.

Value

An updated MKDE list object is returned.

Author(s)

Jeff A. Tracey, PhD
 USGS Western Ecological Research Center, San Diego Field Station
jaTRACEY@USGS.gov
 James Sheppard, PhD
 San Diego Zoo Institute for Conservation Research
jsheppard@sandiegozoo.org

Examples

```
library(terra)
fpath <- system.file("extdata", "dugongdem.RDS", package="mkde")
dugongdem <- terra::readRDS(fpath)
cell.sz <- mean(res(dugongdem))
ext <- ext(dugongdem)
nx <- ncol(dugongdem)
ny <- nrow(dugongdem)
mkde.obj <- initializeMKDE3D(ext$xmin, cell.sz, nx, ext$ymin, cell.sz,
ny, min(values(dugongdem), na.rm=TRUE), 50.0, 15)
mkde.obj <- setMinimumZfromRaster(mkde.obj, dugongdem-20.0)
```

`writeInterpolatedPathVTK`*Write path to VTK.*

Description

Write the interpolated move path to a VTK file.

Usage

```
writeInterpolatedPathVTK(move.dat, mkde.obj, description, filename, control)
```

Arguments

<code>move.dat</code>	A move data object created with <code>initializeMovementData</code>
<code>mkde.obj</code>	An MKDE object created with <code>initialize3DMKDE</code>
<code>description</code>	A text description for the file header
<code>filename</code>	A string for the path and file name
<code>control</code>	A list for finer control

Details

Writes 3D lines between observed locations for move steps. Move steps where the initial location `i` has a value of `FALSE` for `move.dat$use.obs[i]` are omitted. Currently, the list argument `control` only has three elements: (1) “method” with a default value of “linear”, (2) `method.par` which is a list of method parameters, and (3) `z.scale` used to scale the z-coordinates. Only the `z.scale` should be set by the user at this time.

Value

No value is returned

Author(s)

Jeff A. Tracey, PhD
USGS Western Ecological Research Center, San Diego Field Station
<jatracey@usgs.gov>
James Sheppard, PhD
San Diego Zoo Institute for Conservation Research
<jsheppard@sandiegozoo.org>

Examples

```

library(terra)
data(condor)
mv.dat <- initializeMovementData(condor$time, condor$x, condor$y,
z.obs=condor$z, sig2obs=25.0, sig2obs.z=81.0, t.max=65.0)

fpath <- system.file("extdata", "condordem.RDS", package="mkde")
condordem <- terra::readRDS(fpath)
cell.sz <- mean(res(condordem))
ext <- ext(condordem)
nx <- ncol(condordem)
ny <- nrow(condordem)
mkde.obj <- initializeMKDE3D(ext$xmin, cell.sz, nx, ext$ymin, cell.sz,
ny, min(values(condordem), na.rm=TRUE), 30.0, 100)

writeInterpolatedPathVTK(mv.dat, mkde.obj,
"Example California condor move steps", "condor_path.vtk")

# Clean up files
unlink("condor_path.vtk")

```

```
writeObservedLocationVTK
```

Write observed locations to VTK.

Description

Write the observed points to a VTK file.

Usage

```
writeObservedLocationVTK(move.dat, mkde.obj, description, filename, control)
```

Arguments

move.dat	A move data object created with initializeMovementData
mkde.obj	An MKDE object created with initialize3DMKDE
description	A text description for the file header
filename	A string for the path and file name
control	A list for finer control

Details

Writes 3D points for observed locations for move steps. Currently, the list argument control only has one element z.scale used to scale the z-coordinates.

Value

No value is returned

Author(s)

Jeff A. Tracey, PhD
USGS Western Ecological Research Center, San Diego Field Station
<jatracey@usgs.gov>
James Sheppard, PhD
San Diego Zoo Institute for Conservation Research
<jsheppard@sandiegozoo.org>

Examples

```
library(terra)
data(condor)
mv.dat <- initializeMovementData(condor$time, condor$x, condor$y,
z.obs=condor$z, sig2obs=25.0, sig2obs.z=81.0, t.max=65.0)

fpath <- system.file("extdata", "condordem.RDS", package="mkde")
condordem <- terra::readRDS(fpath)
cell.sz <- mean(res(condordem))
ext <- ext(condordem)
nx <- ncol(condordem)
ny <- nrow(condordem)
mkde.obj <- initializeMKDE3D(ext$xmin, cell.sz, nx, ext$ymin, cell.sz,
ny, min(values(condordem), na.rm=TRUE), 30.0, 100)

writeObservedLocationVTK(mv.dat, mkde.obj,
"Example California condor locations", "condor_locations.vtk")

# Clean up files
unlink("condor_locations.vtk")
```

writeRasterToVTK

Write a 2D raster to XDMF XML wrapper and binary data file.

Description

Write the raster to a XDMF files.

Usage

```
writeRasterToVTK(elev, r.rst, g.rst, b.rst, descr, fname)
```

Arguments

elev	A RasterLayer object
r.rst	A RasterLayer object for red
g.rst	A RasterLayer object for green
b.rst	A RasterLayer object for blue
descr	String description to be added to header of VTK file
fname	The path and base file name for output HDF5 files

Details

This function writes a raster to VTK format. The raster is colored according to the RGB values in `r.rst`, `g.rst`, and `b.rst`, respectively. The RGB values must be an integer from 0 to 255.

Value

No value is returned

Author(s)

Jeff A. Tracey, PhD
 USGS Western Ecological Research Center, San Diego Field Station
 <jatracey@usgs.gov>
 James Sheppard, PhD
 San Diego Zoo Institute for Conservation Research
 <jsheppard@sandiegozoo.org>
 Amit Chourasia, MS
 San Diego Supercomputer Center
 <amit@sdsc.edu>

Examples

```
library(terra)
fpath <- system.file("extdata", "condordem120.RDS", package="mkde")
condordem120 <- terra::readRDS(fpath)
elev.val <- values(condordem120)
elev.min <- min(elev.val, na.rm=TRUE)
elev.max <- max(elev.val, na.rm=TRUE)

# make a color lookup table
cmap <- data.frame(value=c(0.0, 0.25, 0.5, 0.75, 1.0),
  R=c(150, 179, 205, 192, 252),
  G=c(224, 204, 205, 183, 243),
  B=c(94, 147, 168, 147, 226))

cmap$value <- cmap$value*(elev.max - elev.min) + elev.min
# red
f.R <- approxfun(cmap$value, cmap$R)
elev.r <- rast(condordem120)
values(elev.r) <- round(f.R(elev.val))
```

```
# green
f.G <- approxfun(cmap$value, cmap$G)
elev.g <- rast(condordem120)
values(elev.g) <- round(f.G(elev.val))
# blue
f.B <- approxfun(cmap$value, cmap$B)
elev.b <- rast(condordem120)
values(elev.b) <- round(f.B(elev.val))
writeRasterToVTK(condordem120, elev.r, elev.g, elev.b, "Elevation for
California condor Example", "condor_dem.vtk")

# Clean up files
unlink("condor_dem.vtk")
```

writeRasterToXDMF *Write a 2D raster to XDMF XML wrapper and binary data file.*

Description

Write the raster to a XDMF files.

Usage

```
writeRasterToXDMF(rast, fname, nodat="NA")
```

Arguments

rast	A RasterLayer object
fname	The path and base file name for output HDF5 files
nodat	A no data character string that will be written in place of no data values.

Details

This function writes XDMF XML wrapper and binary data file.

Value

No value is returned

Author(s)

Jeff A. Tracey, PhD
USGS Western Ecological Research Center, San Diego Field Station
<jatracey@usgs.gov>
James Sheppard, PhD
San Diego Zoo Institute for Conservation Research
<jsheppard@sandiegozoo.org>
Amit Chourasia, MS
San Diego Supercomputer Center
<amit@sdsc.edu>

Examples

```
library(terra)
fpath <- system.file("extdata", "condordem.RDS", package="mkde")
condordem <- terra::readRDS(fpath)

# Save as XDMF (notice no file extension in file name)
writeRasterToXDMF(condordem, "condor_dem")

# Clean up files
unlink("condor_dem.dat")
unlink("condor_dem.xdmf")
```

writeToGRASS

Write MKDE to a GRASS GIS 3D ASCII raster file.

Description

Write the MKDE to a VTK file.

Usage

```
writeToGRASS(mkde.obj, fname, nodat="NA", cumprob=FALSE)
```

Arguments

mkde.obj	3D MKDE object created with <code>initialize3DMKDE</code> and density initialized with <code>initializeDensity</code>
fname	The patch and file name for output VTK file
nodat	A no data character string that will be written in place of no data values.
cumprob	Indicate whether to write the voxel probabilities of cumulative probabilities.

Details

This function writes a GRASS GIS ASCII raster file that can be imported using the `r3.in.ascii` function.

Value

No value is returned

Author(s)

Jeff A. Tracey, PhD
 USGS Western Ecological Research Center, San Diego Field Station
 <jatracey@usgs.gov>
 James Sheppard, PhD
 San Diego Zoo Institute for Conservation Research
 <jsheppard@sandiegozoo.org>

Examples

```

library(terra)
data(condor)
condor <- condor[1:20,] # simply to make example run more quickly
mv.dat <- initializeMovementData(condor$time, condor$x, condor$y,
z.obs=condor$z, sig2obs=25.0, sig2obs.z=81.0, t.max=65.0)

fpath <- system.file("extdata", "condordem120.RDS", package="mkde")
condordem120 <- terra::readRDS(fpath)
cell.sz <- mean(res(condordem120))
ext <- ext(condordem120)
nx <- ncol(condordem120)
ny <- nrow(condordem120)
mkde.obj <- initializeMKDE3D(ext$xmin, cell.sz, nx, ext$ymin, cell.sz,
ny, min(values(condordem120), na.rm=TRUE), cell.sz, 25)

# note: we use a raster coarse integration time step so the
# example runs faster
dens.res <- initializeDensity(mkde.obj, mv.dat, integration.step=10.0)
mkde.obj <- dens.res$mkde.obj
mv.dat <- dens.res$move.dat

# Write file
writeToGRASS(mkde.obj, "ascii3d.txt")

# Clean up files
unlink("ascii3d.txt")

```

writeToVTK

Write MKDE to an ASCII Visualization Tool Kit (VTK) structured grid file.

Description

Write the MKDE to a VTK file.

Usage

```
writeToVTK(mkde.obj, fname, description="3D MKDE", cumprob=FALSE)
```

Arguments

mkde.obj	3D MKDE object created with initialize3DMKDE and density initialized with initializeDensity
fname	The patch and file name for output VTK file
description	A character string with a brief description that will be placed in the header of the VTK file
cumprob	Indicate whether to write the voxel probabilities of cumulative probabilities.

Details

This function writes a VTK structured grid file for a 3D MKDE that can be used in 3D visualization tools such as MayaVI or ParaView

Value

No value is returned

Author(s)

Jeff A. Tracey, PhD
 USGS Western Ecological Research Center, San Diego Field Station
 <jatracey@usgs.gov>
 James Sheppard, PhD
 San Diego Zoo Institute for Conservation Research
 <jsheppard@sandiegozoo.org>

Examples

```
library(terra)
data(condor)
condor <- condor[1:20,] # simply to make example run more quickly
mv.dat <- initializeMovementData(condor$time, condor$x, condor$y,
z.obs=condor$z, sig2obs=25.0, sig2obs.z=81.0, t.max=65.0)

fpath <- system.file("extdata", "condordem120.RDS", package="mkde")
condordem120 <- terra::readRDS(fpath)
# next two lines reduce extent of 2D space to speed execution of example
tmp <- ext(c(range(condor$x) + c(-100, 100), range(condor$y) + c(-100, 100)))
condordem120 <- crop(condordem120, tmp)

cell.sz <- mean(res(condordem120))
ext <- ext(condordem120)
nx <- ncol(condordem120)
ny <- nrow(condordem120)
mkde.obj <- initializeMKDE3D(ext$xmin, cell.sz, nx, ext$ymin, cell.sz,
ny, min(values(condordem120), na.rm=TRUE), cell.sz, 25)

# note: we use a raster coarse integration time step so the
# example runs faster
dens.res <- initializeDensity(mkde.obj, mv.dat, integration.step=10.0)
mkde.obj <- dens.res$mkde.obj
mv.dat <- dens.res$move.dat

# Save as VTK file
writeToVTK(mkde.obj, "condor_3dMKDE.vtk",
description="Example California condor 3D MKDE")

# Clean up files
unlink("condor_3dMKDE.vtk")
```

`writeToXDMF`*Write 3D MKDE to XDMF XML wrapper and binary data file.*

Description

Write the MKDE to a XDMF files.

Usage

```
writeToXDMF(mkde.obj, fname, nodat="NA", cumprob=FALSE)
```

Arguments

<code>mkde.obj</code>	3D MKDE object created with <code>initialize3DMKDE</code> and density initialized with <code>initializeDensity</code>
<code>fname</code>	The path and base file name for output XDMF files
<code>nodat</code>	A no data character string that will be written in place of no data values.
<code>cumprob</code>	Indicate whether to write the voxel probabilities of cumulative probabilities.

Details

This function writes XDMF XML wrapper and binary data file.

Value

No value is returned

Author(s)

Jeff A. Tracey, PhD
USGS Western Ecological Research Center, San Diego Field Station
<jatracey@usgs.gov>
James Sheppard, PhD
San Diego Zoo Institute for Conservation Research
<jsheppard@sandiegozoo.org>
Amit Chourasia, MS
San Diego Supercomputer Center
<amit@sdsc.edu>

Examples

```
library(terra)
data(condor)
condor <- condor[1:20,] # simply to make example run more quickly
mv.dat <- initializeMovementData(condor$time, condor$x, condor$y,
z.obs=condor$z, sig2obs=25.0, sig2obs.z=81.0, t.max=65.0)
```

```
fpath <- system.file("extdata", "condordem120.RDS", package="mkde")
condordem120 <- terra::readRDS(fpath)
cell.sz <- mean(res(condordem120))
ext <- ext(condordem120)
nx <- ncol(condordem120)
ny <- nrow(condordem120)
mkde.obj <- initializeMKDE3D(ext$xmin, cell.sz, nx, ext$ymin, cell.sz,
ny, min(values(condordem120), na.rm=TRUE), cell.sz, 25)

# note: we use a raster coarse integration time step so the
# example runs faster
dens.res <- initializeDensity(mkde.obj, mv.dat, integration.step=10.0)
mkde.obj <- dens.res$mkde.obj
mv.dat <- dens.res$move.dat

# Write file (note no file extension!)
writeToXDMF(mkde.obj, "condor_3dMKDE")

# Clean up files
unlink("condor_3dMKDE.dat")
unlink("condor_3dMKDE.xdmf")
```

Index

- * **datasets**
 - condor, [8](#)
 - dugong, [11](#)
 - panda, [28](#)
- * **package**
 - mkde-package, [2](#)
- computeAreaRaster, [4](#)
- computeContourValues, [5](#)
- computeSizeMKDE, [6](#)
- condor, [8](#)
- deselectLocationsOutsideBounds, [9](#)
- deselectNonMovementSteps, [10](#)
- dugong, [11](#)
- estVarMKDE, [12](#)
- initializeAreaRaster, [13](#)
- initializeDensity, [14](#)
- initializeMKDE2D, [15](#)
- initializeMKDE3D, [17](#)
- initializeMovementData, [18](#)
- mkde (mkde-package), [2](#)
- mkde-package, [2](#)
- mkde2Dgrid, [20](#)
- mkde2Dinteraction, [22](#)
- mkde3Dgrid, [23](#)
- mkde3Dinteraction, [25](#)
- mkdeToRaster, [26](#)
- panda, [28](#)
- plotMKDE, [29](#)
- readdem_example, [30](#)
- setMaximumZfromConstant, [31](#)
- setMaximumZfromRaster, [32](#)
- setMinimumZfromConstant, [33](#)
- setMinimumZfromRaster, [34](#)
- writeInterpolatedPathVTK, [35](#)
- writeObservedLocationVTK, [36](#)
- writeRasterToVTK, [37](#)
- writeRasterToXDMF, [39](#)
- writeToGRASS, [40](#)
- writeToVTK, [41](#)
- writeToXDMF, [43](#)